

1325

Compact in size and high quality printing



Tally DASCOM's 1325 flat-bed serial dot matrix printer, is a 24 pin, 80 column printer with USB and parallel interfaces as standard. The 1325 is ideal for front office applications in retail outlets, travel agents, train stations, banks and doctor's surgeries where space is limited.

With high quality output, an easy to use control panel and the option to use pre-cut or tractor fed paper, the 1325 is ideal for counter-top printing applications such as, tickets, receipts, forms and multi-part documents.

- **Compact 24-pin flat-bed printer**
- **Up to 375 characters per second**
- **Ideal for front office applications**
- **Auto switching USB and parallel interface**
- **Long life ribbon**
- **Small footprint**

The long life ribbon of the 1325 means fewer ribbon changes, less downtime and lower running costs. With print speeds of 375 characters per second (cps) and flexible media handling it keeps transactions smooth and the user happy.

The 1325 is a reliable and easy to use printer, with low running costs and a space saving size.

Available Configuration:

1325 Standard Product

SERIAL MATRIX
PRINTERS

MOBILE
PRINTERS

THERMAL
PRINTERS

LINE MATRIX
PRINTERS

LASER
PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

1325

Print Speed	10 cpi: 375 cps (HSD), 250 cps (Draft), 83 cps (LQ) 12 cpi: 300 cps (Draft), 100 cps (LQ)
Print Method	Serial Impact Dot Matrix
Resolution	Up to 360 x 360dpi
Throughput (ECMA 132)	273 pages per hour
Character Density	10, 12, 15, 17.1, 20cpi, Proportional Spacing
Line Density	1,2,3,4,6,8 lpi
Printhead Life	400 million strokes per pin
Memory	48 Kb
Standard Connectivity	USB 2.0, parallel (Bi-directional)
Standard Emulation	Epson LQ (ESC P/2), IBM ProPrinter (2390 Plus)
Fonts	Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B*, 10 Barcodes
Consumables	Black Ribbon: 7 million characters
STD Paper Handling	Friction and push tractor
Number of Copies	Original +6 (7-part forms)
Paper Type	Continuous forms, cut sheet
Paper Weight	52-100 gsm
Paper Size	55 to 297 mm wide
Physical Weight	Approximately 5 kg
Physical Size	(HxWxD): 203x404x322
Power Voltage	230 V / 50 to 60 Hz
Power Consumption	5.9W MAX in Stand by
Reliability MTBF	10,000 hours
Drivers	Windows 2000, 2003 Server, XP, Vista, Windows 7
Temperature	+0°C to +40°C
Humidity	10% to 90% (not condensing)
Acoustic	< 53dB(A) (ISO 7779)
Warranty	2 years return to base





Note: For OCR applications it is recommended that your readers are tested with print samples supplied by DASCOM prior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operation conditions.

DASCOM GB Limited
ViewPoint, Basing View,
Basingstoke, Hampshire RG21 4RG
Tel: +44 (0) 1256 481481
Fax: +44 (0) 1256 481400

www.dascom.com

All company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Copyright © 2009 DASCOM Europe GmbH
Ver. 1.0
Printed Date: 10/11/2009

SERIAL MATRIX PRINTERS 
MOBILE PRINTERS 
THERMAL PRINTERS 
LINE MATRIX PRINTERS 
LASER PRINTERS 